

BATI XXL SUPERMAT

Waterborne interior acrylic paint -Flat



PRODUCT OVERVIEW

New and maintenance work for walls and ceilings in dry rooms
Residential and commercial sites

BENEFITS

Good hiding power
Odourless
Very quick drying
AFNOR Classification NFT 36 005 Rating Family I Class 7b2

TECHNICAL SPECIFICATIONS

Finish	: flat smooth
Density	: 1.56 +/- 0,05 Kg/l
Solids by	: Weight: 62 +/- 2% Volume: 41 +/- 2%
VOC (directive 2004/42/CE)	: EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 30 g/IVOC
Flash point	: Not applicable
Gloss level at to 85°	: < 10 %
Practical coverage	: 8 to 10 m ² /l per coat depending on surface texture.
Drying time (20°C -65% RH)	: Dry : 2 h Recoat : 4 h
Colours	: White
Storage	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.



BATI XXL SUPERMAT

Waterborne interior acrylic paint -Flat

SURFACE PREPARATION

These recommendations do not override a specific description of the substrate.

APPLICATION

Application conditions	: DTU 59.1
Application equipment	: Brush, Roller, Airless spray-gun.
Clean-up solvent	: Water
Thinner	: Water
Dilution	: Brush (0 to 5 %), Roller (Ready to use), Airless spray-gun (0 to 10 %).

SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
hydraulic binder-based coatings, concrete, plasterboard	Apply 1 coat of BATI XXL PRIM HYDRO	Apply 2 coats of BATI XXL SUPERMAT
plaster	Apply 1 coat of BATI XXL PRIM UNIVERSEL	
previously painted surfaces in good conditions	Apply 1 coat of BATI XXL SUPERMAT diluted to 5 %	

CONTAINER SIZE

15 L

SAFETY MEASURES

Refer to the Safety Data Sheet